


Χαρακτηριστικά



- Posebej zasnovana za vgradnjo v vse vrste vrtljivih vrat. Možni sta dve postavitvi in prilagajanje dimenzij
- Samonosilna konstrukcija ohišja iz pocinkane jeklene plošče, izdelano v strukturni epoksi-poliestrski barvi standardno bele barve RAL9016. Druge barve ali nerjaveče jeklo so na voljo po zahtevi.
- Velika fasetirana rešetka ne potrebuje intenzivnega vzdrževanja.
- Krožne anodizirane aluminijaste izhodna krila, oblikovana po zračnem profilu.
- Centrifugalni ventilatorji z dvojnimi dovodom, ki jih poganja zunanji rotor motorja z nizko raven hrupa. Izbira med 5 hitrostmi. Modeli EC so sestavljeni z ventilatorji z visoko učinkovitostjo in majhno porabo.
- Tip "P" z vodno ogrevano tuljavo. Tip "E" z zaščitnimi električnimi elementi, tremi stopnjami z integrirano regulacijo. Tip "A" brez ogrevanja, samo zrak. Možnost dodatne opremitve z DX tuljavo.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 10m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
 - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
 - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.

Προδιαγραφές

50Hz

Μοντέλο	(m ³ /h)	(m)
ROTO BB 1000 A	5-7	
ROTO BB 1500 A	5-7	
ROTO BB 2000 A	5-7	
ROTO BB 2500 A	5-7	
ROTO SB 1000 A	3,5-5	
ROTO SB 1500 A	3,5-5	
ROTO SB 2000 A	3,5-5	
ROTO SB 2500 A	3,5-5	

Μοντέλο	(m ³ /h)	(kW)	(m)	(kW)
ROTO BB 1000 E	-			
ROTO BB 1500 E	-			
ROTO BB 2000 E	-			
ROTO BB 2500 E	-			
ROTO SB 1000 E	12,44			
ROTO SB 1500 E	-			
ROTO SB 2000 E	-			
ROTO SB 2500 E	-			

Μοντέλο	(m ³ /h)	(m)	(kW)	(kW)	(kW)
ROTO BB 1000 P86	-				
ROTO BB 1500 P86	-				
ROTO BB 2000 P86	-				
ROTO BB 2500 P86	-				
ROTO SB 1000 P86	-				
ROTO SB 1500 P86	-				
ROTO SB 2000 P86	-				
ROTO SB 2500 P86	-				
ROTO BB 1000 P64	-				
ROTO BB 1500 P64	-				
ROTO BB 2000 P64	-				
ROTO BB 2500 P64	-				
ROTO SB 1000 P64	-				
ROTO SB 1500 P64	-				
ROTO SB 2000 P64	-				



Μοντέλο	(m³/h)	(m)	(kW)	(kW)	(kW)
ROTO SB 2500 P64	-				
ROTO BB 1000 P54	36.57				
ROTO BB 1500 P54	15.16				
ROTO BB 2000 P54	38.96				
ROTO BB 2500 P54	24.15				
ROTO SB 1000 P54	14,47				
ROTO SB 1500 P54	21,19				
ROTO SB 2000 P54	30,77				
ROTO SB 2500 P54	36,94				

60Hz

Μοντέλο	(m³/h)	(m)
ROTO BB 1000 A	5-7	
ROTO BB 1500 A	5-7	
ROTO BB 2000 A	5-7	
ROTO BB 2500 A	5-7	

Μοντέλο	(m³/h)	(kW)	(m)	(kW)
ROTO BB 1000 E	-			
ROTO BB 1500 E	-			
ROTO BB 2000 E	-			
ROTO BB 2500 E	-			

Μοντέλο	(m³/h)	(m)	(kW)	(kW)	(kW)
ROTO BB 1000 P86	-				
ROTO BB 1500 P86	-				
ROTO BB 2000 P86	-				
ROTO BB 2500 P86	-				
ROTO BB 1000 P64	-				
ROTO BB 1500 P64	-				
ROTO BB 2000 P64	-				
ROTO BB 2500 P64	-				
ROTO BB 1000 P54	36.57				
ROTO BB 1500 P54	15.16				
ROTO BB 2000 P54	38.96				
ROTO BB 2500 P54	24.15				



ΔΙΑΣΤΑΣΕΙΣ

