

Χαρακτηριστικά

top



- Innovative concept of decorative air curtain based on a recessed model to be installed free-hanging.
- Kliendi soovil on võimalik kujundada esipaneeli erinevate elementidega: logodega, valgustusega, kirjadega või ohutus- ja informatiivsete signaalidega.
- Self-supporting casing construction made of galvanized steel plate painted in grey RAL9006. Muud värvid on ka saadaval (soovi korral).
- Inlet and Outlet inbuilt in the same grid painted in white RAL9016. Muud värvid on ka saadaval (soovi korral).
- Anodeeritud alumiiniumist väljalaskeavad, aerodünaamilise vormiga.
- 2-kiiruselise rootormootoriga juhitud ristvooluventilaatorid, madal müratase.
- "P" type with water heated coil and integrated regulation for ON/OFF or three stages 0-10V proportional valve. "E" tüüp elektriliste varjestatud elementidega, kolm astmed, sisseehitatud reguleerimisvõimalusega. "A" tüüp küttega, ainult ventileerimiseks.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
 - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
 - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.

Προδιαγραφές

50Hz

Μοντέλο	(m³/h)	(m)
TOP 1000 A	3.5	
TOP 1500 A	3.5	
TOP 2000 A	3.5	

Μοντέλο	(m³/h)	(kW)	(m)
TOP 1000 E	3.5		
TOP 1500 E	3.5		
TOP 2000 E	3.5		

Μοντέλο	(m³/h)	(kW)	(m)
TOP 1000 P86	3.5		
TOP 1500 P86	3.5		
TOP 2000 P86	3.5		
TOP 1000 P64	3.5		
TOP 1500 P64	3.5		
TOP 2000 P64	3.5		

ΔΙΑΣΤΑΣΕΙΣ

