

## Χαρακτηριστικά



- Specially designed to be installed on doors of industrial cold stores and freezers with big temperature differences.
- The Twin Kool air curtain system has been designed to offer a versatile solution for any type of cold room. It has two jets of opposing air chambers that create additional space between the chamber and the pre-chamber. Thanks to the double barrier, this model becomes the perfect alternative to the TRIOJET SYSTEM air curtain when space is limited or this model is not an option.
- Samonosilna konstrukcija ohišja iz pocinkane jeklene plošče, izdelano v strukturni epoksi-poliestrski barvi standardno bele barve RAL9016. Druge barve ali nerjaveče jeklo so na voljo po zahtevi.
- Velika fasetirana rešetka ne potrebuje intenzivnega vzdrževanja.
- Anodizirani aluminijasti odhondi ventili oblikovani z zračnim profilom, nastavljivi od 0 do 15 ° na vsaki strani.
- Centrifugalni ventilatorji z dvojnimi dovodom, ki jih poganja zunanji rotor motorja z nizko raven hrupa. Izbira med 5 hitrostmi. Modeli EC so sestavljeni z ventilatorji z visoko učinkovitostjo in majhno porabo.
- Tip "A" brez ogrevanja, samo zrak.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
  - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
  - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.
- Includes varnishing on the PCB to protect it from corrosion.

## Προδιαγραφές

50Hz

| Μοντέλο          | (m <sup>3</sup> /h) | (m) |
|------------------|---------------------|-----|
| TWIN KECG 3000 A | 9,8-13,8            |     |
| TWIN KM 1500 A   | 9,8-13,1            |     |
| TWIN KM 2000 A   | 9,8-13,1            |     |
| TWIN KM 2500 A   | 9,8-13,1            |     |
| TWIN KM 3000 A   | 9,8-13,1            |     |
| TWIN KECM 1500 A | 9,8-13,8            |     |
| TWIN KECM 2000 A | 9,8-13,8            |     |
| TWIN KECM 2500 A | 9,8-13,8            |     |
| TWIN KECM 3000 A | 9,8-13,8            |     |
| TWIN KG 1500 A   | 9,8-13,1            |     |
| TWIN KG 2000 A   | 9,8-13,1            |     |
| TWIN KG 2500 A   | 9,8-13,1            |     |
| TWIN KG 3000 A   | 9,8-13,1            |     |
| TWIN KECG 1500 A | 9,8-13,8            |     |
| TWIN KECG 2000 A | 9,8-13,8            |     |
| TWIN KECG 2500 A | 9,8-13,8            |     |

60Hz

| Μοντέλο          | (m <sup>3</sup> /h) | (m) |
|------------------|---------------------|-----|
| TWIN KECM 1500 A | 9,8-13,8            |     |
| TWIN KECM 2000 A | 9,8-13,8            |     |
| TWIN KECM 2500 A | 9,8-13,8            |     |
| TWIN KECM 3000 A | 9,8-13,8            |     |



ΔΙΑΣΤΑΣΕΙΣ

